Pneumatic Series

Dimensions: 22" x 14" x 14"

Weight: 42 lbs.

HP-Series, pneumatic driven hydrostatic test pumps, available with pressures up to 30,000 PSI. Versatile and compact designs for testing in small confined spaces or remote locations such as on board ships and oil rigs. These units have the ability to start/stop while under pressure.



HP-10 · 10,000 PSI

- Ability to start/stop while under pressure
- Special order options available, built to suit
- Specific units capable of various chemicals, jet fuels
- Dual gauge and high flow options available



HP-20 · 20,000 PSI

| | MODEL | VOLUME | PSI |
|----|------------|-----------|--------|
| C | HP - 6/500 | 6 GPM | 500 |
| 51 | HP - 7/10 | 7 GPM | 1,000 |
| | HP - 35/20 | 3.5 GPM | 2,000 |
| | HP - 25/35 | 2.5 GPM | 3,500 |
| | HP - 1/55 | 1 GPM | 5,500 |
| | HP - 10 | 80 CU IN | 10,000 |
| | HP10-B, V | 240 CU IN | 10,000 |
| | HP10-VT | 240 CU IN | 10,000 |
| | HP - 20 | 80 CU IN | 20,000 |
| | HP - 30 | 80 CU IN | 30,000 |
| | HPD - 7/10 | DUAL PUMP | 10,000 |
| | HPD - 6/35 | DUAL PUMP | 3,500 |
| | HPD - 6/55 | DUAL PUMP | 5,500 |
| | | | |









Shoring Pressure Pumps • Hand Pumps



100 PSI AIR needing only standard shop air

ROLL CAGE enclosed in a rugged roll cage of heavy gauge welded steel

HOSE 8' high pressure outlet hose

INLINE STRAINER stainless 100 mesh strainer, for pump protection from debris

GAUGE stainless steel liquid filled, ensures less flutter, with accurate readings







HP6/500 · 500 PSI

A C C E S S O R I E S

FHWA-1

Pressure wand accessory makes your fire hose tester a year round contributor to your equipment fleet.



Wheel & Handle Kits

Truly the most portable test pumps on the market, RICE makes available an optional sturdy wheel and handle kit.







Pressure Feed Tanks

The pressure tank assembly, an accessory designed to allow the force-feeding of diaphragm test pumps.

3500 Arrowhead Drive Carson City, Nevada 89706 web site:

www.ricehydro.com

e-mail:

ricehydro@ricehydro.com

Toll Free U.S. & Canada:

(800) 245-4777

Phone:

(775) 885-1280

Fax:

(800) 998-7423